

STRATA SUPERIOR WELDING PRODUCTS

ADVANCETIG205ACDC



200A AC/DC PFC INVERTER TIG / MMA WELDER

Featuring the latest IGBT and active PFC technology the ADVANCETIG 205AC/DC is reliable, easy to use and energy efficient. Designed tough with IP23 and high quality, overspecified components - this machine is made for rugged NZ workshops and onsite tasks.

- · IGBT inverter technology for smooth & stable welding output and increased reliability
- · Increased duty cycle and energy efficiency with active PFC technology
- · Multi voltage input wiill operate with wide range of input voltage, can even be used with long extension leads
- Industrial IP23 casing with front panel protection resists damage, moisture and corrosion
- Microprocessor control system for superior and dynamic arc characteristics
- · Lightweight & compact design, ideal for portable applications
- Extreme stress tested in production up to 440V, ensuring rugged reliability
- · Lift TIG and HF start modes gives versatility when welding around sensitive electronic equipment
- · Electronic HF TIG arc ignition system, contamination free and easy arc starting with low EMF interference
- 2T/4T multi-level trigger control modes
- · Dual digital display megters for accurate pre-setting and feedback of welding parameters and output
- · Durable and reliable with high quality & over specified electronic components
- · Intelligent protection system with temperature, voltage and current sensors for increased reliability and safety
- Designed to work with generator power supply with protection from power surges.
- Multi PCB construction is economical to service and repair compared to single PCB design
- All remote functions connect through single plug 12 pin connection
- Quick connect inlet gas fitting
- Accessories include 3m earth lead with heavy duty earth clamp, 4m MMA lead with heavy duty twist lock electrode holder, Strata Professional PRO-GRIP26 25ft TIG torch with thumbwheel remote control, 2 stage flowmeter, argon gas regulator, 4m gas hose, gas inlet quick connector and hose clamps.

| | B | W | IGBT INVERTER TECHNOLOGY | | <u>1</u> рн 230V | 6 15^ |
|-----------------------------------|------------------------|-----------------------------|--------------------------------|-------------------------------------|------------------------------|-----------------|
| ALTERNATING/ DIRECT CURRENT | CORROSION RESISTANT | SPIKE/ Generator Safe | IGBT INVERTER TECHNOLOGY | INTELLIGENT PROTECTION SYSTEM | 230V 50HZ SINGLE PHASE | 15 AMP PLUG |

| DIMENSIONS (LxWxH) | WEI | GHT | input i Sup | | INPUT F Sup Toler | PLY | MAXI INPUT C | | GENEF Capa | | MMA, AO Curi Out | | mma Volt | | MMA Cyc | | | A DUTY Cle | DC TIG CYC | | TIG UP SLO Down Slo Adjustme |
|-----------------------|----------------------------|----------------|----------------|----------------|-------------------------|------------------|-----------------|---------------------|---------------|-------------|------------------------|--------------|-------------|-------------|------------|-----------------------|------|---------------|----------------|------------|------------------------------------|
| 492 x 189 x 350mm | 15 | kg | 230V A 50/6 | AC 15A ioHz | 90 - 27 | 5V AC | 32 | 2A | 8k' | VA | 5 - 2 | 00A | 67 | V | | @22% @60% @100% | | @60% @100% | 200A@ 140A@ | 22% 60% | 0-10s |
| FLOW/PI | s Post Re-Flow Tment | TIG P Frequ | | TIG P WIDTH | | AC WAVE | | a Frequ Adjus | JENCY | INSUL CL | ATION ASS | POV EFFIC | | POW FACT | | STAND | ARDS | MM ROD S | | WARR | ANTY |
| 0-2/0 | D-10s | 0.5 - 2 | 200Hz | 5 - 9 | 95% | Square Sine \ | | 50-2 | 50Hz | IP | 23 | 80 | % | 0.9 | 99 | EN609 20 | | 1.6 - 5 | i.0mm | 36 mo | nths |

www.strata.co.nz





TIG WELDING ACCESSORIES & CONSUMABLES

Standard Collets

| CODE: D | ESCRIPTION: |
|------------|-----------------------|
| TC10N23 | 1.6mm Standard Collet |
| WT-TC10N24 | 2.4mm Standard Collet |
| TC10N25 | 3.2mm Standard Collet |

Standard Collet Bodies

| TCB10N31 | 1.6mm Standard Collet Body |
|-------------|----------------------------|
| WT-TCB10N32 | 2.4mm Standard Collet Body |
| TCB10N28 | 3.2mm Standard Collet Body |

Standard Ceramic Cups

| TCC10N46 | 1/2" Standard Ceramic Cup |
|----------|----------------------------|
| TCC10N47 | 7/16" Standard Ceramic Cup |
| TCC10N48 | 3/8" Standard Ceramic Cup |

Mild Steel TIG Rods

ER70S-6 Grade.

| WT-TR16MS-70S-6 | 1.6mm x 1m Mild Steel TIG Rods |
|-----------------|--------------------------------|
| TR24MS-70S-6 | 2.4mm x 1m Mild Steel TIG Rods |
| TR32MS-70S-6 | 3.2mm x 1m Mild Steel TIG Rods |

Aluminium TIG Rods

| TR16AL-5356 | 1.6mm x 1m Aluminium TIG Rods |
|----------------|-------------------------------|
| WT-TR24AL-5356 | 2.4mm x 1m Aluminium TIG Rods |
| TR32AL-5356 | 3.2mm x 1m Aluminium TIG Rods |

Stainless Steel TIG Rods

• 316 Grade.

| WT-TR16SS-316 | 1.6mm x 1m Stainless Steel TIG Rods |
|---------------|-------------------------------------|
| TR24SS-316 | 2.4mm x 1m Stainless Steel TIG Rods |
| TR32SS-316 | 3.2mm x 1m Stainless Steel TIG Rods |

Industrial Welding Trolley

- Suitable for ADVANCETIG 205ACDC/325 and water cooling unit or industrial storage unit
- Super duty wheels and castors
- Includes gas bottle chains and takes 'G' size gas bottles.

22108 Industrial Welding Trolley - V2

Compact Welding Trolley

- · Capable of holding 'G' size gas bottles.
- 17384 Industrial Welding Trolley



Tungsten Electrodes




HYUND

- Zirconiated for use on aluminium
- Thoriated for use on stainless and mild steel

| TT16-150 | 1.6mm x 150mm Thoriated Tungsten Electrodes |
|-------------|---|
| WT-TT24-150 | 2.4mm x 150mm Thoriated Tungsten Electrodes |
| TT32-150 | 3.2mm x 150mm Thoriated Tungsten Electrodes |
| TZ16-150 | 1.6mm x 150mm Zirconiated Tungsten Electrodes |
| WT-TZ24-150 | 2.4mm x 150mm Zirconiated Tungsten Electrodes |
| TZ32-150 | 3.2mm x 150mm Zirconiated Tungsten Electrodes |

MMA Welding Electrodes



Water Coolers

- Suitable for ADVANCETIG machines with a water cooled torch set up (not incl.)
- · Induction motor with safety pressure switch.

| 22109 | Industrial Integrated Water Cooler 400V | - |
|-------|---|---|
| | w/ Connection Cable | |

Industrial Storage Unit

- Fits in industrial welding trolley (#22108)
- 620 x 420 x 290mm
- Convenient storage for welding wire, electrodes, gloves and welding accessories.

22115 Industrial Storage Unit - V2



HYUNDAL

www.strata.co.nz

rd Optional